

CODAN 40 W Ku Band RBUC - MODEL 7940



Available for sale beginning 2008!

 [Download CODAN 40 W Ku-Band RBUC - MODEL 7940 Technical specifications \(146 kB\)](#)

Revolutionary Design Platform

- **Output Power 40 W at PI dB minimum**
- **48 V DC Operation**
- **Power Consumption of BUC <400 W**
- **DC Power Consumption ~450 W**
- **< 8 kg**
- **360 L x 182 W x 165 H mm**
- **Optional Universal Antenna Feed Mounting Kit**
- **14.0–14.5 GHz and 13.75–14.5 GHz**
- **Non-Inverting LOs 13050 and 12800 MHz**
- **Ideally suited to Rapid Deployment or Offshore Applications**
- **Uniquely-designed Cooling System**
- **DC Power via Separate Connector**
- **Same rugged design as all Codan Products**
- **Available in Single Thread & 1+1 Redundant Configurations**
- **Includes entire feature set of existing Codan LBUC family**
- **Identical accessories of existing Codan LBUC family**
- **Common Mounting Kits**
- **Common Serial, Dry-Contact & FSK Interfaces for M&C**
- **Common External Dimensions**
- **Common Redundancy Switching Systems**
- **Separate Power Supply available for AC Power applications**
- **Ethernet Monitor and Control (not available with initial release)**
- **Three Year Warranty**
- **Global Customer Support Network**

CODAN 40 W Ku Band RBUC - MODEL 7940

http://vsat-buc.at-communication.com/en/codan/40w_rbuc.html